

# PassLeader

PassLeader

> Contact Us    Login / Register    Search...

HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

CART (1)



Try **PDF Demo** before you buy

We're not the only ones **happy** about PassLeader Practice Material ...

63159+ customers in 100+ countries use PassLeader Test Engine. Meet our customers.

VOREED

GetCustom

JET ORANGE

iCompany

Paradoxx

iMessenger



<http://www.passleader.top/>

Latest Exam Guide & Learning Materials

**Exam :** PD0-001

**Title :** CompTIA PDI+ Beta Exam

**Vendors :** CompTIA

**Version :** DEMO

NO.1 Which of the following type of lamp is used for heating a fuser?

- A.Xenon
- B.Halogen
- C.Incandescent
- D.Light Emitting Diode

Answer: B

NO.2 When arriving at the customers location, two different users describe the problem, and from their description it seems to be two separate problems. Which of the following is an appropriate step to take?

- A.Ignore both of them and decide what the real problem is.
- B.Set up a separate call for each problem.
- C.Have them duplicate the problem at the device.
- D.Ask a third person and see if the problem is the same thing.

Answer: C

NO.3 An encoder sensor typically detects:

- A.paper position.
- B.shaft rotation.
- C.magnetic flux.
- D.laser beam strength.

Answer: B

NO.4 Which of the following functions is associated with the developer unit?

- A.Supplies toner to the photoconductor
- B.Charges the surface of the photoconductor
- C.Writes the latent image on the photoconductor
- D.Cleans the photoconductor

Answer: A

NO.5 In which of the following sections of an MFP would a technician find a Xenon Lamp?

- A.The paper feed section
- B.The fuser section
- C.The scanner section
- D.The transfer section

Answer: C

NO.6 Which of the following would be the BEST process for the technician to follow when beginning to diagnose a unit at a customers site?

- A. Check the printers error log, and then inform the primary user what the issue is.
- B. Go directly to the printer and investigate any issues that are found.
- C. Investigate the printers status, then ask the primary user to write down what they think is wrong.
- D. Gather information from the primary user, and then evaluate the printers condition.

Answer: D

NO.7 A polygon mirror is part of which of the following assemblies?

- A. Laser unit
- B. Developer unit
- C. Charge assembly
- D. Fuser assembly

Answer: A

NO.8 Which of the following devices can route electrical signals only when activated by an external control signal?

- A. Solenoid
- B. Relay
- C. Clutch
- D. Capacitor

Answer: B

NO.9 The polygon mirror is located in which of the following components?

- A. Developer unit
- B. Scanner unit
- C. Fuser unit
- D. Laser unit

Answer: D

NO.10 How should a service representative provide closure at the end of a call for a client?

- A. Explain the issues of the call, the steps taken to resolve them and query the client if they have any additional needs.
- B. Explain the solution to the issue and then provide the client with the technicians contact

information in  
case they have any questions.

C. Give the client a technical explanation on the issue and how it was fixed; throw any faulty equipment in the clients garbage.

D. Proceed to the next service call, check back with the client in a week to see if they have any additional needs.

Answer: A

NO.11 Which of the following utilities could be used to determine a subnet mask?

A. PING

B. NSLOOKUP

C. TRACERT

D. IPCONFIG

Answer: D

NO.12 When onsite repairing a printer the technicians cell phone rings and it is a personal call, how should the technician handle this?

A. Answer the call and talk to your friend at the customer site.

B. Answer the call and tell the friend you will call them later.

C. Let it go to voicemail, call them back between service calls.

D. Let it ring and call the friend back when the customer leaves.

Answer: C

NO.13 Which of the following is the FIRST step a technician should take when troubleshooting a device issue?

A. Gather information from the customer.

B. Isolate the problem on the device.

C. Read the service documentation for possible causes.

D. Check the parts life counters.

Answer: A

NO.14 Which of the following is a reason black toner is used in color printers?

A. It decreases the print speed in color laser printers.

B. It prevents moir patterns when printing color photographs.

C.It reduces the cost per page when printing gray scale documents.

D.It makes the color toner resistant to smudging when wet.

Answer: C

NO.15 A technician is troubleshooting a network connectivity issue on a MFD and would like to eliminate the possibility of another device on the network having the same IP address. The technician should:

A.disconnect the MFD and ping the IP address.

B.disconnect the MFD and ping the subnet mask.

C.disconnect the MFD and ping the loopback address.

D.run the ipconfig command from the command prompt.

Answer: A

NO.16 Scheduled preventative maintenance visits should be carried out:

A.after two unplanned service calls.

B.according to manufacturers specifications.

C.when the device is becoming unreliable.

D.every sixty days.

Answer: B

NO.17 Using the CMYK color model, the color purple is produced by combining cyan and which other color?

A.Green

B.Magenta

C.Yellow

D.Black

Answer: B

NO.18 The customer has a dedicated ink jet fax machine that is used to send and receive faxes only from the corporate office. The user complains of streaks on the received faxes while the internal self-prints are fine.

Which of the following should a technician recommend?

A.Clean the scanner glass on the distant machine.

B.Clean the scanner glass on the local machine.

C.Clean the printer head on the local machine.

D.Call the telephone company to increase the line signal level.

Answer: A

NO.19 When is it advisable to dump the waste toner from a technicians service vacuum?

- A.When it is full.
- B.It is not recommended.
- C.Before performing preventative maintenance.
- D.After each call.

Answer: B

NO.20 A customer is concerned about excessive media jamming in their device. Which of the following is the

FIRST thing a technician should check?

- A.Media feed rollers
- B.Cassette drawers
- C.Fusing section
- D.Device log data

Answer: D

NO.21 Which of the following types of media would MOST likely cause above normal amounts of machine jamming?

- A.Envelopes
- B.Colored media
- C.Letterhead
- D.Pre punched

Answer: A

NO.22 The proper safety guidelines for handling any device specific consumables can be found in which of

the following documentation?

- A.Material Safety Data Sheets
- B.Installation Guides
- C.Consumer Reports
- D.Devices Parts Catalog

Answer: A

NO.23 How many CCDs are located in a single pass duplex ADF?

- A.One

B.2

C.3

D.4

Answer: B

NO.24 Which of the following stages in the laser print process attracts toner to the latent image on the photoconductor?

A.Writing

B.Fusing

C.Development

D.Transfer

Answer: C

NO.25 Which of the following failed components would be responsible for the fuser unit not heating properly?

A.Halogen lamps

B.Ball bearing

C.Hot roller

D.Pressure roller

Answer: A

NO.26 Which of the following components is part of the ink dispersion system?

A.Print Heads

B.Cleaning heads

C.Pickup Roller

D.Charge Assembly

Answer: A

NO.27 A customer has installed a new computer on their network. They can print to the printer but the option for duplex printing is not available. All other computers have the option. Which of the following is the cause of the problem?

A.The new computer is printing to the wrong IP address.

B.The new computer is using the wrong protocol.

C.The driver port is not setup correctly.

D.The option has not been selected on the driver.

Answer: D

NO.28 Which of the following is the purpose of a torque limiter in a roller?

- A.To reduce wear and tear on rollers.
- B.To provide resistance but still allow some slippage.
- C.To limit the amount of movement by media.
- D.To make it easier to replace rollers.

Answer: B

NO.29 Which of the following items can be used as a discharge lamp?

- A.Halogen lamp
- B.Light Emitting Diodes (LED)
- C.Fuser lamp
- D.Cleaning roller

Answer: B

NO.30 During the photoconductor preparation step, residual charge can be removed by which of the following? (Select TWO).

- A.Pressure
- B.Oil
- C.Light
- D.Gravity
- E.Electrical Charge

Answer: CE